

Rhino™ 4200

DYMO®



Compact, Time-Saving Label Maker for On-The-Go Pros

- Familiar computer-style keyboard with country-specific layout for fast and easy text entry
- One-Touch “Hot Keys” provide shortcuts for creating and formatting wire/cable wraps, flags, Code 39 and Code 128 bar codes, fixed-length, general and breaker labels
- “Favorites” key provides single-key access to your most commonly used labels, symbols and terms
- Avoid repeated steps with the “Custom” key – customize and save settings for individual label formats
- Pre-programmed library with 150 symbols and terms for security, electrical, pro A/V, and facilities management
- Integrated rubber bumpers help prevent damage from accidental drops and falls
- Large back-lit display is easy to read, even in dimly-lit work areas
- Prints 57% faster than the competition*

*Based on independent testing of Rhino 4200 vs. Brother PT-1400 and Brother PT-7100 in default settings



TAPES



Rechargeable Battery Pack

Single Unit Includes:

- Rhino 4200 Label Maker
- 12 mm White Vinyl Label Cartridge
- Quick Reference Guide



Kit includes everything in single unit plus:

- Carry Case
- Rechargeable Battery
- AC Charging Adaptor



Quick Specs

| | |
|-----------------------------|-------------------------------------|
| Unit Dimensions (H x W x L) | 215 x 103 x 57 mm |
| Weight (excluding battery) | 540 g |
| Mac®/PC Compatible | No |
| Accepts Label Sizes | 6mm, 9mm, 12mm, 19mm |
| Tape Platform | IND Rhino™ |
| Resolution | 180 dpi |
| Printing System | Thermal Transfer |
| Print Speed | 15mm/sec |
| Barcodes | Yes, Code 39 & Code 128 |
| Cutter Type | Manual |
| Batteries | 6 AA or Rechargeable (not included) |
| AC Adapter | Yes (not included) |
| Networking | No |
| Country of Origin | China |

| Item Number | Description | | Length (cm) | Width (cm) | Height (cm) | Weight (kg) | QTY | EAN | Customer Price |
|-------------|-----------------------------|--------|-------------|------------|-------------|-------------|-----|----------------|----------------|
| S0955950 | RHINO 4200 UK/IRL | Unit | 8.8 | 15.6 | 23.0 | 0.7 | 1 | 3501170955956 | |
| | | Shelf | - | - | - | - | - | - | |
| | | Case | 23.0 | 20.0 | 35.0 | 3.2 | 4 | 13501170955953 | |
| | | Pallet | 120.0 | 80.0 | 120.0 | 216.3 | 240 | - | |
| Accessories | | | | | | | | | |
| S0721430 | RHINO AC Adapter | Unit | 11.5 | 5.9 | 8.9 | 0.2 | 1 | 5411313400756 | |
| S0895840 | Rechargeable battery | Unit | 8.5 | 3.2 | 8.9 | 0.1 | 1 | 3501170895849 | |
| | | | | | | | | | |
| S0955950 | KITCASE R4200 QWERTY UK/IRE | Unit | 9.2 | 27.5 | 26.5 | 1.1 | 1 | 3501178529920 | |
| | | Shelf | - | - | - | - | - | - | |
| | | Case | 29.0 | 28.0 | 29.0 | 3.8 | 3 | 13501170841393 | |
| | | Pallet | 120.0 | 80.0 | 15.0 | 25.0 | 180 | - | |

dymo.com

Rhino™ 4200 | Compatible Labels



IND Vinyl

Ideal for both indoor and outdoor applications. Available in the widest range of colors that meet OSHA, ANSI and ISO color standards.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -40°C to 80°C

IND Flexible Nylon

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -10°C to 80°C

IND Permanent Polyester

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.

- UL recognized component to UL 969
- RoHS compliant
- For flat surfaces only
- Temperature rating: -40°C to 150°C

IND Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables.

- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- UL recognized as a component to UL 224
- RoHS compliant
- Temperature rating: -55° C to 135°C

| IND Compatible Labels | | | | | | | | | | | | |
|-------------------------|--------|---------|----------|-------|-------|---------|---------|---------|---------|---------|---------|---------|
| Width | Length | A | A | A | A | A | A | A | A | A | A | A |
| IND VINYL | | | | | | | | | | | | |
| 9mm | 5.5m | 18443 | - | - | - | - | - | 1805437 | - | - | - | - |
| 12mm | | 18444 | - | 18432 | 18435 | 1805413 | 1805416 | 1805435 | 1805414 | 1805243 | 1805415 | 1805412 |
| 19mm | | 18445 | - | 18433 | 18436 | 1805419 | 1805422 | 1805436 | 1805420 | 1805417 | 1805421 | 1805418 |
| IND PERMANENT POLYESTER | | | | | | | | | | | | |
| 6mm | 5.5m | 1805442 | 1805440 | - | - | 1805441 | - | - | - | - | - | - |
| 9mm | | 18482 | 18508DM0 | - | - | 18485 | - | - | - | - | - | - |
| 12mm | | 18483 | 622289 | - | - | 18486 | - | - | - | - | - | - |
| 19mm | | 18484 | 622290 | - | - | 18487 | - | - | - | - | - | - |
| IND FLEXIBLE NYLON | | | | | | | | | | | | |
| 12mm | 3.5m | 18488 | - | 18490 | - | - | - | - | - | - | - | - |
| 19mm | 3.5m | 18489 | - | 18491 | - | - | - | - | - | - | - | - |
| IND HEAT-SHRINK TUBE | | | | | | | | | | | | |
| 6mm | 1.5m | 18051 | - | 18052 | - | - | - | - | - | - | - | - |
| 9mm | | 18053 | - | 18054 | - | - | - | - | - | - | - | - |
| 12mm | | 18055 | - | 18056 | - | - | - | - | - | - | - | - |
| 19mm | | 18057 | - | 18058 | - | - | - | - | - | - | - | - |

Country of Origin: Belgium

DISTRIBUTED BY:
Newell Europe Sàrl
Chemin de Blandonnet 10
1214 Vernier – Switzerland
WWW.DYMO.COM

13-0103

INTERNAL USE ONLY. NOT FOR DISTRIBUTION.

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.



A Newell Rubbermaid Brand

©2014 Newell Europe LLC